

CST-1500 SEED TENDER

The CST-1500 is one of the largest tenders on the market. This five compartment tender is able to transport fertilizer and seed at the same time. The use of conveyors, ensure no seed damage or cross-contamination, unloading at a rate of 2 tons per minute.

This tender will reduce your seeding down time significantly while providing versatile use year round. Weigh and transport seed to your air seeder in spring, unload grain from your combine during harvest and haul product to the market any time.



FEATURES

- Tier 4, diesel engine
- 5 compartments
- Stainless steel slave conveyor construction
- Stainless steel slopes & gates
- 12 gauge hopper construction
- Two stage - epoxy/polyurethane coating system
- Internal cat walk
- 20" wide, slave conveyor belt
- 25' 7" long, 16" paddle belt, unload conveyor
- Self-contained hydraulics
- Aluminum anodized hydraulic valves
- Camera package
- LED working lights
- Access holes
- External ladders
- 2 sight glasses per compartment
- LED gate indicators
- Air ride trailer
- Aluminum outer wheels with polyethylene fenders

OPTIONAL FEATURES

- Full Centrifugal Fan system

APPLICATIONS

- Grain
- Seed
- Fertilizer

Model	Discharge Heights Min/Max		Swing Diameter	Empty Weight	M3 / Comp. (Total)	Bushels / Comp. (Total)	Compartment Capacity** Metric	Total Capacity ** Metric
CST-1500	8' 8" @ 15° 19' 1" @ 40°	2.6m @ 15° 5.8m @ 40°	144° Swing 42' 7" (12.9m) Reach	25640 lb (11.6 t)	7.8m3 (39.1m3)	222 (1110)	7.8 MT ea.	39 MT

BTS-2950 SEED TENDER

Our bean tenders are designed to efficiently move grain, pulse crops, fertilizer, or any granular material. The tender can be purchased with it's own trailer, or mounted to any flatbed truck or trailer for convenient transportation.

Fill any planter, including centre fill models, fast and effortlessly. The unloading conveyor can be swung from front to back, down the driver side.



FEATURES

- 5.5 hp petrol engine
- Manual roll tarp
- 2 button remote control
- Ladders, front and rear

APPLICATIONS

- Seed
- Fertilizer
- Load Planters

OPTIONAL FEATURES

- Full wireless remote
- Weigh scale package
- Extendable downspout
- Trailer with electric brakes

Model	Conveyor Size		Overall Length	Hopper Length	Hopper Height	Hopper Width	Discharge Height	Conveyor Height	Conveyor Swing	Empty Weight (Trailer Not Incl.)	Total Bushels	Total Tonnes
BTS-2950	21' 8" Tube 10" Belt	6.4m Tube 0.2m Belt	24' 7" (7.5m)	11' 11" (3.6m)	8' 5" (2.6m)	8' 5" (2.6m)	8' 3" (2.5m)	10' (3m)	140°	1.3 t	235	6.4 t