

## TILIO HYDRAULIC DRIVE





## THE **NEW, SAFE, & INNOVATIVE** LINE OF AUGERS FROM **MERIDIAN**

Meridian is proud to introduce the new line of TL10 Hydraulic Drive Truck Load Augers

The TL10's hydraulic drive system offers several key advantages over traditional belt-driven augers:

**Fewer Moving Parts:** With no large belts, pulleys, driveshaft, or gearbox, there are fewer components to wear out, replace, or maintain, keeping your operation running longer with less downtime.

**Improved Safety:** Eliminating high-speed belts and exposed driveshafts significantly reduces the risk of injury during operation, making your farm a safer place to work.

The TL10 is built for performance and peace of mind. combining simplicity, reliability, and safety in one rugged unit. Powered by a 40HP Vanguard motor, it will move up to 2.25 tons/minute.










## **FEATURES:**

10" Diameter Tube
3/16" Gauge Super-Edge™ Continuous Flighting
40HP Vanguard Engine
Hydraulic Drive
4 Wheel Mover Kit
Powder Coat Finish
2.25 Tons/Minute Capacity



		10-39	10-46	10-53	10-59
Α	RAISED	23' 2'' - 7.07m	24' 2'' - 8.3m	31' - 9.47m	34' 4'' - 10.47m
	LOWERED	9' 4'' - 2.85m	10' 11'' - 3.33m	11' 5'' - 3.49m	12' 3'' - 3.74m
В	RAISED	12' 11" - 3.95m	15' 7" - 4.77m	17' 9'' - 5.41m	19' 11'' - 6.07m
	LOWERED	7' 9'' - 2.36m	9' 3'' - 2.82m	9' 8'' - 2.95m	10' 6'' - 3.21m
С	RAISED	17' 2'' - 5.24m	20' 11'' - 6.39m	23' 9'' - 7.24m	27' 1'' - 8.27m
	LOWERED	21' 3'' - 6.49m	26' 2'' - 7.98m	29' 10'' - 9.09m	34' 5'' - 10.37m
D	RAISED	12' 4'' - 3.78m	14' 7'' - 4.46m	17' 2'' - 5.24m	19' 10'' - 6.06m
	LOWERED	15' 1'' - 4.61m	17' 5'' - 5.33m	20' 5'' - 6.24m	22' 10'' - 6.96m
E		11' 7'' - 3.55m	7' 6'' - 2.30m	14' 1'' - 4.3m	20' 8'' - 6.3m
F		25' 3'' - 7.70m	36' 8" - 11.19m	36' 8'' - 11.19m	26' 8'' - 11.19m
AUGER HITCH WEIGHT		300lbs	320lbs	360lbs	260lbs



www.grainlogic.com.au Phil Haeusler 0429 323 227 and Alexander Haeusler 0404 331 058